

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

10/531367

(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/040617 A2(51) International Patent Classification⁷:

H01L

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/TB2003/006480

(22) International Filing Date: 20 October 2003 (20.10.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0224300.4

20 October 2002 (20.10.2002) GB

(71) Applicant (*for all designated States except US*): BOREALIS TECHNICAL LIMITED [—/—]; Montagu Pavilion, 8-10 Queensway, Gibraltar (GI).(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— without international search report and to be republished upon receipt of that report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): TAVKHELIDZE, Avto [GE/GE]; c/o Borealis Technical Limited, Montagu Pavilion, 8-10 Queensway, Gibraltar (GI). TSAKADZE, Leri [GE/GE]; c/o Borealis Technical Limited, Montagu Pavilion, 8-10 Queensway, Gibraltar (GI).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: THERMOELECTRIC MATERIAL WITH INTEGRATED DE BROGLIE WAVE FILTER



(57) Abstract: In this invention we offer a method which blocks movement of low energy electrons through the thermoelectric material. We achieve this using filter which is more transparent for high energy electrons than for low energy ones. Tunnel barrier on the way of the electrons is used as filter. Filter works on the basis of the wave properties of the electrons. The geometry of the tunnel barrier is such that barrier becomes transparent for electrons having certain de Broglie wavelength. If the geometry of the barrier is such that its transparency wavelength matches the wavelength of high energy electrons it will be transparent for high energy electrons and will be blocking low energy ones by means of tunnel barrier.

BEST AVAILABLE COPY

WO 2004/040617 A2

Thermoelectric Material with Integrated de Broglie Wave Filter

Technical Field

The present invention relates to thermoelectric materials.

5 Background Art

Up to date thermoelectric generators and refrigerators have low efficiency. One of the main reasons for this low efficiency is that all free electrons around and above the Fermi level take part in current transport through the thermoelectric material, but it is only high energy electrons that are
10 efficiently used for cooling and energy generation.

Figure 1 shows a simple diagrammatic representation of a thermoelectric couple known in the art in which a p-type material is connected to an n-type material via a conducting bridge, and electrons flow through the device, pumping heat from one side of the couple to the other. Other configurations
15 and combinations of materials are also used. As mentioned already, the low efficiency of such arrangements arises from the fact that all the free electrons around and above the Fermi level take part in current transport through the thermoelectric material and consequently external current source makes work which is not efficiently used for heat transfer.

20 In US Patent US6281514 a method for promoting the passage of electrons through a potential barrier comprising providing a potential barrier having a geometrical shape for causing de Broglie interference is disclosed. This results in the increase of tunneling through the potential barrier.

This approach does not contemplate using such a potential barrier for
25 controlling or filtering which electrons contribute to current transport through the thermoelectric materials.

Figure 2 shows two domains are separated by a surface 36 having an indented or protruded shape, with height a .

An incident probability wave 30 is reflected from surface 36 to give
30 reflected probability wave 32, and from the bottom of the indent to give reflected probability wave will equal to zero for waves having wavelength $\lambda=4a/(1+2n)$ where $n=0, 1, 2, \dots$. Further this means that the electron will not reflect back from the border, and will leak through the potential barrier with increased probability.

-2-

Indents or protrusions on the surface should have dimensions comparable to de Broglie wavelength of electron. In particular indent or protrusion height should be

$$a = \lambda(1+2n)/4$$

5 And the indent or protrusion width should be much greater than λ .

In this invention we offer a method which blocks movement of low energy electrons through the thermoelectric material. We achieve this using filter which is more transparent for high energy electrons than for low energy ones. Tunnel barrier on the way of the electrons is used as filter. Filter works on
10 the basis of the wave properties of the electrons. The geometry of the tunnel barrier is such that barrier becomes transparent for electrons having certain de Broglie wavelength. If the geometry of the barrier is such that its transparency wavelength matches the wavelength of high energy electrons it will be transparent for high energy electrons and will be blocking low energy
15 ones by means of tunnel barrier.

Disclosure of Invention

In one aspect, the present invention comprises a method for filtering electrons, allowing the most energetic ones to travel freely through a thermoelectric material whilst at the same time blocking low energy electrons
20 and preventing them from taking part in current transport. This is achieved by creating a tunnel barrier or filter on the 'anode' surface of a thermoelectric material having a geometric pattern comprising indentations or protrusions. The dimensions of the indents or protrusions are such that electrons below a certain energy are reflected by the tunnel barrier or
25 filter, whilst electrons above a certain energy are able to pass through the tunnel barrier or filter. Specifically, the depth of the indents or height of protrusions is $\lambda(1+2n)/4$, where λ is the de Broglie wavelength of an electron having the fore-mentioned certain energy.

In a second aspect, the present invention comprises a thermoelectric material
30 having a tunnel barrier or filter on its 'anode' surface, in which the tunnel barrier or filter has a geometric pattern comprising indentations or protrusions. The dimensions of the indents or protrusions are such that electrons below a certain energy are reflected by the tunnel barrier or filter, whilst electrons above a certain energy are able to pass through the
35 tunnel barrier or filter. Specifically, the dimensions of the indents or

-3-

protrusions are $\lambda(1+2n)/4$, where λ is the de Broglie wavelength of an electron having the fore-mentioned certain energy.

In a further aspect, the present invention comprises a thermoelectric device comprising a first thermoelectric material and a second thermoelectric material, and having a tunnel barrier or filter interposed between the first material and the second material, in which the tunnel barrier or filter has a geometric pattern comprising indentations or protrusions. The dimensions of the indents or protrusions are such that electrons below a certain energy are reflected by the tunnel barrier or filter, whilst electrons above a certain energy are able to pass through the tunnel barrier or filter. Specifically, the dimensions of the indents or protrusions are $\lambda(1+2n)/4$, where λ is the de Broglie wavelength of an electron having the fore-mentioned certain energy.

In a yet further aspect, the present invention comprises a thermoelectric device comprising a first thermoelectric material, a second thermoelectric material, and one or more tunnel barriers or filters, in which the tunnel barriers or filters have a geometric pattern comprising indentations or protrusions. The dimensions of the indents or protrusions are such that electrons below a certain energy are reflected by the tunnel barriers or filters, whilst electrons above a certain energy are able to pass through the tunnel barriers or filters. Specifically, the dimensions of the indents or protrusions are $\lambda(1+2n)/4$, where λ is the de Broglie wavelength of an electron having the fore-mentioned certain energy.

Brief Description of Drawings

Figure 1 shows in diagrammatic form, a typical prior art thermoelectric device;

Figure 2 shows in diagrammatic form, an incident probability wave, two reflected probability waves and a transmitted probability wave interacting with a surface having a series of indents (or protrusions);

Figure 3 shows in a diagrammatic form a tunnel barrier or filter of the present invention;

Figure 4 shows in diagrammatic form several configurations for thermoelectric devices of the present invention.

Best Mode for Carrying Out the Invention

In the following, reference is made to indented and protruded cross-sections, geometries and surfaces. It is to be understood that for the purpose of the

-4-

present invention that these terms are considered to be equivalent, and, for example, that the height of a protrusion is equivalent to the depth of an indent.

5 The present invention concerns the use of tunnel barriers or filters for controlling current transport in thermoelectric materials and devices. The tunnel barriers or filters have a stepped geometry comprising indents or protrusions in which the depth of the steps is such that high-energy electrons cannot reflect back from the step-like structure because of interference of de Broglie waves. Consequently high-energy electrons have to
10 tunnel through the barrier. Low energy electrons have longer wavelengths and they can reflect back from the step-like structure. Thus the tunnel barrier partially stops low energy electrons and is more transparent for high-energy electrons because of wave nature of the electron. The effect of introducing an indented or protruded surface in this way is that the tunnel barrier stops
15 low energy electrons and is transparent for high energy ones.

Referring now to Figure 3, which depicts one embodiment for a tunnel barrier of the present invention, two materials 40 and 42 are separated by the thin electrical insulator material 44. The insulator material can be any one of a number of materials such as SiO_2 , Si_3N_4 , Al_2O_3 or titanium oxide. Materials 40
20 and 42 may be the same or different, and may be either semiconductors or metals. A variety of suitable semiconductors are known and include Bi_2Te_3 and its Sb- and Se- doped phases, $\text{Bi}_{1-x}\text{Sb}_x$, and CoSb . The interface 46 between materials 40 and 42 is indented/protruded as shown. The depth of the indentations at this interface are a , and the width is much more than λ ,
25 where λ is the de Broglie wavelength. Typically a is in the range of $10-100\lambda$. The value for a is chosen to set a threshold energy value above which the barrier is transparent to electron flow, and below which electron flow is prevented.

The insulating layer may be formed by a number of means known to the art
30 including including sputter deposition, vacuum evaporation, chemical vapor deposition (CVD), electrochemical deposition. Thus deposition of the insulating layers such as SiO_2 , Si_3N_4 , Al_2O_3 etc., may be achieved using thermal evaporation or sputtering methods, or the growth of native oxides.

The films are synthesized by pulsed laser deposition where the crystallinity
35 can be controlled by the deposition temperature.

-5-

In a preferred embodiment, an indented/protruded structure is formed on the surface of material 40. This may be achieved by a number of methods known to the art, as disclosed above and may also include pulsed laser deposition where the crystallinity can be controlled by the deposition temperature. In a second step, insulating material 44 is deposited over the indented/protruded surface so formed or grown as insulating oxide of 40. In a third step, material 42 is attached to the indented/protruded surface so formed. Again, this may be achieved by a number of methods known to the art, including deposition and electrochemical growth.

Thermoelectric devices comprising the barrier are also contemplated. Figure 4 shows several thermoelectric devices of the present invention having an n-type material 50, a p-type material 52, conductors 56 and an external circuit 58 and power source 59. A barrier or filter 54 is in electrical contact with the 'anode' end of the p-type and n-type materials, and is also in electrical contact with a conductor. Figure 4a shows a device having two barriers or filters, Figure 4b shows a device having a barrier or filter attached to the anode end of the n-type material, and Figure 4c shows a device having a barrier or filter attached to the anode end of the p-type material.

Industrial Applicability

The tunnel barrier of the present invention may be utilized in a number of thermoelectric devices for improving their efficiency. For example the use of the tunnel barrier will increase the cooling capacity of Peltier devices, as well as improving the generation of electricity by thermoelectric generators.


Claims

1. A tunnel barrier for controlling the movement of an electron through a thermoelectric material comprising a potential barrier having an indented or protruded cross-section.
- 5 2. The tunnel barrier of claim 1 wherein the depth of indents in said indented cross-section or the height of protrusions in said protruded cross-section is chosen to set a threshold energy value above which the barrier is transparent to electron flow, and below which electron flow is prevented
- 10 3. The tunnel barrier of claim 1 wherein the depth of indents in said indented cross-section or the height of protrusions in said protruded cross-section is given by the relationship $\lambda(1+2n)/4$, where λ is the de Broglie wavelength of said electron, and where n is 0 or a positive integer.
- 15 4. The tunnel barrier of claim 3 in which n is an integer having a value between 0 and 4.
5. The tunnel barrier of claim 1 wherein the width of indents in said indented cross-section or the width of protrusions in said protruded cross-section the width is much more than λ , where λ is the de Broglie wavelength.
- 20 6. The tunnel barrier of claim 1 in which said potential barrier comprises an electrical insulator.
7. A thermoelectric device comprising:
 - a) a first thermoelectric material;
 - 25 b) a second thermoelectric material;
 - c) the tunnel barrier of claim 1.
8. The thermoelectric device of claim 7 wherein said first thermoelectric material comprises an n-type material, said second thermoelectric material comprises a p-type material, and wherein a tunnel barrier of claim 1 is in electrical contact with the anode of said n-type material and the cathode of said p-type material.
- 30

-7-

9. The thermoelectric device of claim 7 wherein said first thermoelectric material comprises an n-type material, said second thermoelectric material comprises a p-type material in electrical contact with said n-type material, and wherein a tunnel barrier of claim 1 is in electrical contact with the anode of said p-type material.
- 5
10. The thermoelectric device of claim 7 wherein said first thermoelectric material comprises an n-type material, said second thermoelectric material comprises a p-type material, and wherein a tunnel barrier of claim 1 is in electrical contact with the anode of said n-type material and a further tunnel barrier of claim 1 is in electrical contact with the anode of said p-type material.
- 10
11. A method for making the thermoelectric device of claim 7 comprising:
- (a) forming an indented or protruded structure on a surface of a first thermoelectric material;
 - (b) forming an insulating material over said indented or protruded surface;
 - (c) attaching a second thermoelectric material to said insulating material.
- 15
12. The method of claim 11 in which said step of forming an insulating material comprises depositing said insulating material.
- 20
13. The method of claim 11 in which said step of forming an insulating material comprises oxidising said first material.
14. The method of claim 11 in which said step of forming an indented or protruded structure comprises etching.
- 25
15. The method of claim 11 in which said step of forming an indented or protruded structure comprises ablation.

1/4

Figure 1

2/4

Figure 2








Figure 3

Figure 4aFigure 4bFigure 4c

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



10/531367



(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/040617 A3

(51) International Patent Classification⁷: H01L 35/00,
35/30

(21) International Application Number:
PCT/IB2003/006480

(22) International Filing Date: 20 October 2003 (20.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0224300.4 20 October 2002 (20.10.2002) GB

(71) Applicant (for all designated States except US): BORE-
ALIS TECHNICAL LIMITED [—/—]; Montagu Pavil-
ion, 8-10 Queensway, Gibraltar (GI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): TAVKHELIDZE,
Avto [GE/GE]; c/o Borealis Technical Limited, Montagu
Pavilion, 8-10 Queensway, Gibraltar (GI). TSAKADZE,
Leri [GE/GE]; c/o Borealis Technical Limited, Montagu
Pavilion, 8-10 Queensway, Gibraltar (GI).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

[Continued on next page]

(54) Title: THERMOELECTRIC MATERIAL WITH INTEGRATED DE BROGLIE WAVE FILTER



(57) Abstract: In this invention we offer a method which blocks movement of low energy electrons through the thermoelectric material. We achieve this using filter which is more transparent for high energy electrons than for low energy ones. Tunnel barrier on the way of the electrons is used as filter. Filter works on the basis of the wave properties of the electrons. The geometry of the tunnel barrier is such that barrier becomes transparent for electrons having certain de Broglie wavelength. If the geometry of the barrier is such that its transparency wavelength matches the wavelength of high energy electrons it will be transparent for high energy electrons and will be blocking low energy ones by means of tunnel barrier.

WO 2004/040617 A3

WO 2004/040617 A3



(88) Date of publication of the international search report:
19 August 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

In International Application No

/IB 03/06480

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 H01L35/00 H01L35/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, INSPEC, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	SUNGTAEK JU Y ET AL: "STUDY OF INTERFACE EFFECTS IN THERMOELECTRIC MICROREFRIGERATORS" JOURNAL OF APPLIED PHYSICS, AMERICAN INSTITUTE OF PHYSICS. NEW YORK, US, vol. 88, no. 7, 1 October 2000 (2000-10-01), pages 4135-4139, XP001049040 ISSN: 0021-8979 page 4138, right-hand column, paragraph 3 - page 4139, left-hand column, paragraph 1	1,7,9
X	WO 02/47178 A (IBM UK ; IBM (US)) 13 June 2002 (2002-06-13) figure 14 ----- -/--	1,2, 6-12,14

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* ~~document which~~ may throw doubts on priority claim(s) or ~~used to establish the publication date of another~~ ~~other special reason (as specified)~~
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

24 June 2004

Date of mailing of the international search report

05/07/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Kirkwood, J

INTERNATIONAL SEARCH REPORT

International Application No

IB 03/06480

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 281 514 B1 (TAVKHELIDZE AVTO) 28 August 2001 (2001-08-28) cited in the application the whole document	1-15
A	HISHINUMA Y ET AL: "Refrigeration by combined tunneling and thermionic emission in vacuum: Use of nanometer scale design" APPL. PHYS. LETT. (USA), APPLIED PHYSICS LETTERS, 23 APRIL 2001, AIP, USA, vol. 78, no. 17, 23 April 2001 (2001-04-23), pages 2572-2574, XP002285946 ISSN: 0003-6951 the whole document	1-15
A	US 5 023 671 A (DIVINCENZO DAVID P ET AL) 11 June 1991 (1991-06-11) the whole document	1-15
A	WO 00/59047 A (THERMODYNE TECHNOLOGIES INC) 5 October 2000 (2000-10-05) the whole document	1-15
A	EP 0 437 654 A (DAHLBERG REINHARD) 24 July 1991 (1991-07-24) the whole document	1-15
A	PATENT ABSTRACTS OF JAPAN vol. 0153, no. 87 (E-1117), 30 September 1991 (1991-09-30) & JP 3 155376 A (JAPAN ATOM POWER CO LTD:THE), 3 July 1991 (1991-07-03) abstract	1-15
A	PATENT ABSTRACTS OF JAPAN vol. 0176, no. 72 (E-1474), 10 December 1993 (1993-12-10) & JP 5 226704 A (MATSUSHITA ELECTRIC IND CO LTD), 3 September 1993 (1993-09-03) abstract	1-15
A	DE 34 04 137 A (DAHLBERG REINHARD) 8 August 1985 (1985-08-08) the whole document	1-15
A	DE 38 18 192 A (DAHLBERG REINHARD) 7 December 1989 (1989-12-07) the whole document	1-15

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No.

/IB 03/06480

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0247178	A	13-06-2002	US 2002092557 A1	18-07-2002
			AU 2082302 A	18-06-2002
			EP 1364416 A2	26-11-2003
			WO 0247178 A2	13-06-2002
			TW 538514 B	21-06-2003
US 6281514	B1	28-08-2001	AU 2762199 A	23-08-1999
			EP 1058947 A1	13-12-2000
			WO 9940628 A1	12-08-1999
			US 6531703 B1	11-03-2003
			US 6495843 B1	17-12-2002
US 5023671	A	11-06-1991	DE 69002845 D1	30-09-1993
			DE 69002845 T2	17-03-1994
			EP 0389761 A1	03-10-1990
			JP 2533218 B2	11-09-1996
			JP 3016270 A	24-01-1991
WO 0059047	A	05-10-2000	AU 762276 B2	19-06-2003
			AU 6045700 A	16-10-2000
			CA 2367686 A1	05-10-2000
			CN 1351764 T	29-05-2002
			EP 1166369 A1	02-01-2002
			JP 2002540636 T	26-11-2002
			WO 0059047 A1	05-10-2000
			US 2003184188 A1	02-10-2003
			US 6489704 B1	03-12-2002
			US 6396191 B1	28-05-2002
EP 0437654	A	24-07-1991	EP 0437654 A1	24-07-1991
JP 3155376	A	03-07-1991	JP 2670366 B2	29-10-1997
JP 5226704	A	03-09-1993	NONE	
DE 3404137	A	08-08-1985	DE 3404137 A1	08-08-1985
DE 3818192	A	07-12-1989	DE 3818192 A1	07-12-1989

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.